
North America's Leader in Hazardous Material Information Management
1905 Aston Avenue, Carlsbad, CA 92008
Phone (800) 451-8346 Fax (760) 602-8888

MSDS PRODUCT INFORMATION

Date: 10/07/2005
To: MSDS Requester
From: 3E Company
Subject: The MSDS you have requested

☐ MSDS NOT REQUIRED

In response to your request for a Material Safety Data Sheet, according to the OSHA Hazard Communication Standard (Right-to-Know), the following item is an article. Articles are defined in 29 CFR 1910.1200(c). Products such as Drugs, cosmetics, food, or alcoholic beverages, wood or wood products, and tobacco or tobacco products, as defined in 29 CFR 1910.1200(b)(6), are exempt from the Hazard Communication Standard. Items that are considered articles, as defined in 29 CFR 1910.1200(c), are also exempt from this Standard. Therefore, the manufacturer is not required to provide an MSDS for this product.

☒ MSDS DISCONTINUED PRODUCT

In response to your request for a Material Safety Data Sheet, the manufacturer has discontinued the product listed below. The MSDS Attached is the most current version, or an MSDS is no longer available.

☐ MSDS BEST COPY AVAILABLE

The MSDS attached is the best copy available from the manufacturer.

☐ MANUFACTURER NO LONGER IN BUSINESS

In response to your request for a Material Safety Data Sheet, a current MSDS could not be obtained for this product. It has been determined that the manufacturer listed below is no longer in business. A current address and phone number could not be located.

Manufacturer: Borden, Inc.

Product Name: Elmer's Clear Floor Tile Adhesive (Latex) (DISCONTINUED)



MATERIAL SAFETY DATA SHEET

Consumer Products Division, Division of Borden, Inc.
180 EAST BROAD STREET, COLUMBUS, OHIO 43215

For ordering information, additional copies of MSDS, etc., 800-848-9400
For technical information only, 614-431-6680

Emergency Telephone
(614) 431-6600

THE OSHA HAZARD COMMUNICATION STANDARD 29 CFR 1910.1200 REQUIRES THAT
THE INFORMATION CONTAINED ON THIS SHEET BE MADE AVAILABLE TO YOUR WORKERS.

INSTRUCT YOUR WORKERS TO HANDLE THIS PRODUCT PROPERLY

NAME: **ELMER'S CLEAR FLOOR TILE ADHESIVE (LATEX)**
TYPE: **SYNTHETIC LATEX RESIN EMUL**
APPLICATION: **INTERIOR FLOOR COVERING ADHESIVE; ITEMS E-892, E-893**

11-Dec-86

SIGNAL WORD—CAUTION

THIS MATERIAL PRESENTS POSSIBLE HEALTH HAZARDS AS DETERMINED WHEN REVIEWED ACCORDING TO THE REQUIREMENTS OF THE
OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION 29 CFR PART 1910.1200 "HAZARD COMMUNICATION" STANDARD.

CHEMICAL HAZARD RATING

HEALTH=1 (SLIGHT)
FIRE=0 (LEAST)
REACTIVITY=0 (LEAST)
CHRONIC=*

29CFR1910.1200 HAZARDOUS INGREDIENTS/REPORTED HEALTH EFFECTS

CAS REGISTRY NO. MATERIAL DESCRIPTION % RANGE

67-56-1 METHANOL 1-5

* POSSIBLE REPRODUCTIVE HAZARD FROM PROLONGED EXPOSURE.
MAY CAUSE BLINDNESS IF SWALLOWED.
CAN CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION. SIGNS AND
SYMPTOMS MAY INCLUDE HEADACHE, DIZZINESS, NAUSEA, VOMITING
AND DROWSINESS. -- SEE FOOTNOTE(S) C
ACGIH TLV: SKIN-200 PPM (260 MG/M3) TWA: 250 PPM (310 MG/M3) STEL
OSHA PEL: 200 PPM (260 MG/M3) TWA
NIOSH DOCUMENT NUMBER 76-148

1330-20-7 XYLENE 1-5

OVEREXPOSURE MAY CAUSE LIVER DAMAGE.
OVEREXPOSURE MAY CAUSE KIDNEY DAMAGE.
CAN CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION. SIGNS AND
SYMPTOMS MAY INCLUDE HEADACHE, DIZZINESS, NAUSEA, VOMITING,
UNCONSCIOUSNESS AND EVEN ASPHYXATION. -- SEE FOOTNOTE(S) C
ACGIH TLV: 100 PPM (435 MG/M3) TWA: 150 PPM (655 MG/M3) STEL
OSHA PEL: 100 PPM (435 MG/M3) TWA
NIOSH DOCUMENT NUMBER: 75-168

FOOTNOTE C: AS OF THE DATE OF ISSUANCE OF THIS DOCUMENT, THIS
MATERIAL HAS NOT BEEN LISTED BY NTP, IARC OR OSHA AS A
CARCINOGEN.

PHYSICAL DATA

SPECIFIC GRAVITY -- 1.04
PERCENT VOLATILES -- 45
APPEARANCE -- OFF-WHITE PASTE
ODOR -- MILD LATEX

ACUTE HEALTH HAZARD DATA

SKIN ABSORPTION: NOT TOXIC DERMALLY WHEN TESTED AS DESCRIBED IN
16 CFR PART 1500.3 (c) (1) AND (2).
INGESTION: NOT TOXIC ORALLY WHEN TESTED AS DESCRIBED IN 16 CFR
PART 1500.3 (c) (1) AND (2).
INHALATION: NOT TOXIC BY INHALATION WHEN TESTED AS DESCRIBED IN
16 CFR PART 1500.3 (c) (1) AND (2); HOWEVER, OVEREXPOSURE MAY
CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION. ALSO, CONTAINS
MATERIALS WHICH, IF ALLOWED TO BECOME AIRBORNE, MAY CAUSE
IRRITATION OF NOSE, THROAT AND LUNGS.
SKIN: NOT AN IRRITANT WHEN TESTED AS DESCRIBED IN 16 CFR PART
1500.41.
EYES: SLIGHTLY IRRITATING WHEN TESTED AS DESCRIBED IN 16 CFR PART
1500.42.

HANDLING PRECAUTIONS

INHALATION: AVOID PROLONGED OR REPEATED BREATHING OF VAPOR.
EYES: AVOID PROLONGED OR REPEATED CONTACT WITH EYES.
HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY
PRACTICES. THESE PRACTICES INCLUDE AVOIDING UNNECESSARY
EXPOSURE AND REMOVAL OF THE MATERIAL FROM EYES, SKIN AND
CLOTHING.
WASH THOROUGHLY AFTER HANDLING.

EMERGENCY AND FIRST AID PROCEDURES

INGESTION: IF ACCIDENTALLY SWALLOWED, DILUTE BY DRINKING LARGE
QUANTITIES OF WATER. IMMEDIATELY CONTACT POISON CONTROL
CENTER OR HOSPITAL EMERGENCY ROOM FOR ANY OTHER ADDITIONAL
TREATMENT DIRECTIONS.
INHALATION: REMOVE TO FRESH AIR.
EYE CONTACT: FLUSH THOROUGHLY WITH WATER. IF IRRITATION
PERSISTS, CALL A PHYSICIAN.

FIRE AND EXPLOSION HAZARD DATA

WILL NOT BURN UNLESS WATER HAS EVAPORATED.
IN CASE OF FIRE, USE WATER SPRAY, DRY CHEMICAL, FOAM OR CO2. USE
WATER TO KEEP FIRE-EXPOSED CONTAINERS COOL.

REACTIVITY DATA

NORMALLY STABLE AS DEFINED IN NFPA 704-12 (4-3.1)

CONTROL MEASURES

IF AIRBORNE CONTAMINANTS ARE GENERATED WHEN THE MATERIAL IS
HEATED OR HANDLED, SUFFICIENT VENTILATION IN VOLUME AND AIR
FLOW PATTERNS SHOULD BE PROVIDED TO KEEP AIR CONTAMINANT
CONCENTRATION LEVELS BELOW ACCEPTABLE CRITERIA.

PERSONAL PROTECTION INFORMATION

WHERE AIR CONTAMINANTS CAN EXCEED ACCEPTABLE CRITERIA, USE
NIOSH/MSHA APPROVED RESPIRATORY PROTECTION EQUIPMENT.
RESPIRATORS SHOULD BE SELECTED BASED ON THE FORM AND
CONCENTRATION OF CONTAMINANTS IN AIR IN ACCORDANCE WITH
OSHA 29 CFR 1910.134 OR OTHER APPLICABLE STANDARDS OR
GUIDELINES.

SPILL OR LEAK PROCEDURES

SWEEP (SCOOP) UP AND REMOVE.
PREVENT ENTRY INTO NATURAL BODIES OF WATER.

WASTE DISPOSAL METHOD

DISPOSE OF ACCORDING TO LOCAL, STATE, AND FEDERAL REQUIREMENTS

STORAGE PRECAUTIONS

KEEP CONTAINER CLOSED.
STORE IN A COOL, DRY PLACE.

DOT CLASSIFICATION

NOT REGULATED.

BORD-00-0106.01

DISCLAIMER

SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY BORDEN, except that the product shall conform to contracted specifications, and that the product does not infringe any valid United States patent. The information provided herein was believed by Borden to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of product and to determine the suitability of the product for its intended use. Buyer's exclusive remedy shall be for damages and no claim of any kind, whether as to product delivered or for non-delivery of product, and whether based on contract, breach of warranty, negligence or otherwise shall be greater in amount than the purchase price of the quantity of product in respect of which damages are claimed. In no event shall Seller be liable for incidental or consequential damages, whether Buyer's claim is based on contract, breach of warranty, negligence or otherwise.